




Mounting of Peninsula Desks w/End Panel


Recommended Tools



Hardware Used




Installers: To properly install the Flux Peninsula Desk product you will need a floor plan to assure proper installation. Peninsula Desk require a secondary height credenza with factory installed mounting.




Step 1 Review the Layout

- The product offers two different locations to mount the peninsula desk to the secondary height credenza. The layout plan should indicate the correct mounting location. Guide lines in this step will explain the flush mount location or the offset mount location.




Flush Mount Location **A**
back panel of top support flush with back panel of credenza




Offset Mount Location **B**
back panel of top support inset 5" from back panel of credenza


Layout with an overhead cabinet requires the offset mounting location. If using the wall panels the offset location mounting location is also recommended.



layouts with overhead cabinets require offset mount location



layouts with wall mounts items, recommend using offset mount location




offset mount locations increases overall layout footprint by approximately 5"

Notice To Installers: Failure to comply with installation instructions will compromise the safety, durability and performance of this product, which may risk injury to the user of this product and/or diminish the product life cycle. Jasper Group assumes no liability in these instances.

Peninsula Desks with End Panel *continued*

Step 2 Mounting the Peninsula Desk

(Note: Prior to performing Step 3 check for options see next page for Option A)



Step 2

Mounting the Peninsula Desk

- Align the correct mounting holes on the “double” T support with the holes on the credenza top
position = flush mount location **A**
- position = offset mount location **B**
- Fasten peninsula desk from inside the cabinet using $\frac{5}{16}$ ” x $1\frac{1}{2}$ ” hex head bolts with washer into the bottom of the “double” T support.
- Finish leveling the product using the adjustable glides located on the end leg assembly or the post frame assembly

Notice To Installers: Failure to comply with installation instructions will compromise the safety, durability and performance of this product, which may risk injury to the user of this product and/or diminish the product life cycle. Jasper Group assumes no liability in these instances.



JASPER
GROUP
BRAND

jsifurniture.com
800.457.4511

812.482.3204 O
812.482.1548 F

225 Clay Street / PO Box 231
Jasper, Indiana 47546

Form No. INST-FL007
010/2/18